

Float Sub IBOP (Inside Blow Out Preventer)

Series #	Valve Configuration	ID (inches)	OD (inches)	Float Size	Pressure (PSI)	Weight (lbs)	Length (inches)	Alternate Threads
D2375-FS	2 3/8 Eue Pin by Box	1.500	3.375	1F2R	5000	50	23	
D2875-FS	2 7/8 Eue Pin by box	1.500	3.500	1F2R	5000	60	26	
D3500-FS	3 1/2 Eue Pin by Box	2.250	4.500	3F	5000	115	33	
D2375IF-FS	2 3/8 IF Pin by Box	1.500	3.375	1F2R	5000	50	23	
D2875IF-FS	2 7/8 IF Pin by Box	1.875	4.250	2F-3R	5000	80	24.5	2 7/8 AOH, 2 7/8 SLH-90
D3500IF-FS	3 1/2 IF Pin by Box	1.875	5.000	2F-3R	7500	125	25.5	4 FH
D3500DS40-FS	DS40 Pin by Box	1.875	5.250	2F-3R	7500	175	32.5	
D4500IF-FS	4 1/2 IF pin by Box	2.375	6.375	4R	7500	170	21.5	4 1/2 XH, 4 1/2 H90
D5250FH-FS	5 1/2 FH Pin by Box	3.250	7.250	5F-6R	7500	330	35	